

# 2013 Consumer Security Products Performance Benchmarks (Edition 3)

**Antivirus, Internet Security & Total Security Windows 7** 

**January 2013** 

**Document:** 2013 Consumer Security Products Performance Benchmarks (Edition 3)

Authors: M. Baquiran, D. Wren
Company: PassMark Software
Date: 22 January 2013

Edition: 3

File: totalprotectionsuites-jan2013.docx

# **Table of Contents**

TABLE OF CONTENTS	2
REVISION HISTORY	4
REFERENCES	4
EXECUTIVE SUMMARY	<u> </u>
OVERALL SCORE	
PRODUCTS AND VERSIONS	
Internet Security Software	
Antivirus Software	
Total Security Software	
PERFORMANCE METRICS SUMMARY	11
INTERNET SECURITY SOFTWARE (HDD) – TEST RESULTS	14
BENCHMARK 1 – BOOT TIME	14
BENCHMARK 2 – SCAN TIME	15
BENCHMARK 3 – USER INTERFACE LAUNCH TIME	16
Benchmark 4 – Memory Usage during System Idle	17
BENCHMARK 5 – BROWSE TIME	18
BENCHMARK 6 – INTERNET EXPLORER LAUNCH TIME	19
BENCHMARK 7 – INSTALLATION TIME	20
Benchmark 8 – Installation Size	21
Benchmark 9 – Registry Keys Added	22
BENCHMARK 10 – FILE COPY, MOVE AND DELETE	23
BENCHMARK 11 – INSTALLATION OF THIRD PARTY APPLICATIONS	24
BENCHMARK 12 – NETWORK THROUGHPUT	25
BENCHMARK 13 – FILE FORMAT CONVERSION	26
BENCHMARK 14 – FILE COMPRESSION AND DECOMPRESSION	27
BENCHMARK 15 – FILE WRITE, OPEN AND CLOSE	28
BENCHMARK 16 – PE SCAN TIME	29
BENCHMARK 17 – FILE COPY DISK TO DISK	30
ANTIVIRUS SOFTWARE (HDD) – TEST RESULTS	31
BENCHMARK 1 – BOOT TIME	31
Benchmark 2 – Scan Time	32
BENCHMARK 3 – USER INTERFACE LAUNCH TIME	33
BENCHMARK 4 – MEMORY USAGE DURING SYSTEM IDLE	34
BENCHMARK 5 – BROWSE TIME	35
BENCHMARK 6 – INTERNET EXPLORER LAUNCH TIME	36
BENCHMARK 7 – INSTALLATION TIME	37
BENCHMARK 8 – INSTALLATION SIZE	38
Benchmark 9 – Registry Keys Added	39
BENCHMARK 10 – FILE COPY, MOVE AND DELETE	
BENCHMARK 11 – INSTALLATION OF THIRD PARTY APPLICATIONS	41

BENCHMARK 12 – NETWORK THROUGHPUT	42
BENCHMARK 13 – FILE FORMAT CONVERSION	43
BENCHMARK 14 – FILE COMPRESSION AND DECOMPRESSION	44
BENCHMARK 15 – FILE WRITE, OPEN AND CLOSE	45
BENCHMARK 16 – PE SCAN TIME	46
BENCHMARK 17 – FILE COPY DISK TO DISK	47
TOTAL SECURITY SOFTWARE (HDD) – TEST RESULTS	48
BENCHMARK 1 – BOOT TIME	48
BENCHMARK 2 – SCAN TIME	48
BENCHMARK 3 – USER INTERFACE LAUNCH TIME	49
BENCHMARK 4 – MEMORY USAGE DURING SYSTEM IDLE	49
BENCHMARK 5 – BROWSE TIME	50
BENCHMARK 6 – INTERNET EXPLORER LAUNCH TIME	50
BENCHMARK 7 – INSTALLATION TIME	51
BENCHMARK 8 – INSTALLATION SIZE	51
Benchmark 9 – Registry Keys Added	52
BENCHMARK 10 – FILE COPY, MOVE AND DELETE	52
BENCHMARK 11 – INSTALLATION OF THIRD PARTY APPLICATIONS	53
BENCHMARK 12 – NETWORK THROUGHPUT	53
BENCHMARK 13 – FILE FORMAT CONVERSION	54
BENCHMARK 14 – FILE COMPRESSION AND DECOMPRESSION	54
BENCHMARK 15 – FILE WRITE, OPEN AND CLOSE	55
BENCHMARK 16 – PE SCAN TIME	55
BENCHMARK 17 – FILE COPY DISK TO DISK	56
INTERNET SECURITY SOFTWARE (SSD) – TEST RESULTS	57
BENCHMARK 1 – BOOT TIME	57
BENCHMARK 2 – SCAN TIME	57
BENCHMARK 10 – FILE COPY, MOVE AND DELETE	58
BENCHMARK 17 – FILE COPY DISK TO DISK	58
DISCLAIMER AND DISCLOSURE	59
CONTACT DETAILS	59
APPENDIX 1 – TEST ENVIRONMENT	60
APPENDIX 2 – METHODOLOGY DESCRIPTION	61

# **Revision History**

Rev	Revision History	Date
Edition 1	Initial version of this report.	31 August 2012
Edition 2	Added newly tested products.	2 November 2012
Edition 3	Added newly tested products.	15 January 2013

# References

Ref#	Document	Author	Date
1	What Really Slows Windows Down (URL)	O. Warner, The PC Spy	2001-2009

## **Executive Summary**

PassMark Software® conducted objective performance testing on ten (10) Internet Security software products, fourteen (14) Antivirus software products, and five (5) Total Security software products on Windows 7 Ultimate Edition (64-bit) SP1 between July 2012 and January 2013. This report presents our results and findings as a result of performance benchmark testing conducted for these consumer security products.

Subsequent editions of this report will include new products released for 2013 as they are made available. For more details on which versions were tested, please see the section "Products and Versions".

Note that throughout this report, categories marked with "(HDD)" and "(SSD)" were tested with a Hard Disk Drive and a Solid State Drive used as the main boot drive respectively.

Testing was performed on all products using seventeen (17) performance metrics. These performance metrics are as follows:

- Boot Time;
- Scan Time;
- · User Interface Launch Time;
- Memory Usage during System Idle;
- Browse Time;
- Internet Explorer Launch Time;
- Installation Time;
- Installation Size;
- Registry Keys Added;
- File Copy, Move and Delete;
- Installation of Third Party Applications;
- Network Throughput (previously named "Binary Download Test")
- File Format Conversion;
- File Compression and Decompression;
- File Write, Open and Close;
- · PE Scan Time and; and
- File Copy Disk to Disk.

Testing in the SSD configuration was performed on five (5) Internet Security products using four (4) of the above metrics. These performance metrics are as follows:

- Boot Time;
- Scan Time;
- File Copy, Move and Delete and; and
- · File Copy Disk to Disk.

### **Overall Score**

PassMark Software assigned every product a score depending on its ranking in each metric compared to other products in the same category.

#### **Internet Security Software (HDD)**

In the following table the highest possible score attainable is 170; in a hypothetical situation where a product has attained first place all 17 metrics. Internet Security products have been ranked by their overall scores:

Product Name	Overall Score
Norton Internet Security 2013	132
Kaspersky Internet Security 2013	128
AVG Internet Security 2013	114
Trend Micro Titanium Internet Security 2013	98
Avast! Internet Security 7	86
F-Secure Internet Security 2013	81
Panda Internet Security 2013	80
G Data InternetSecurity 2013	79
BitDefender Internet Security 2013	72
McAfee Internet Security 2013	65

#### **Antivirus Software (HDD)**

In the following table the highest possible score attainable is 238; in a hypothetical situation where a product has attained first place in all 17 metrics. Antivirus products have been ranked by their overall scores:

Product Name	Overall Score
Kaspersky Anti-Virus 2013	164
Norton AntiVirus 2013	153
AVG Anti-Virus Free 2013	144
Microsoft Security Essentials	139
Avast! Pro Antivirus 7	134
Panda Cloud Antivirus FREE	131
Panda Antivirus Pro 2013	130
AVG Anti-Virus 2013	129
Quick Heal Pro Antivirus 2013	123
Avira Antivirus Free 2013	122
G Data AntiVirus 2013	118
Trend Micro Titanium 2013	105
Avast! Free Antivirus 7	103
McAfee Antivirus Plus 2013	87

#### **Total Security Software (HDD)**

In the following table the highest possible score attainable is 85; in a hypothetical situation where a product has attained first place in all 17 metrics. Total Security products have been ranked by their overall scores:

Product Name	Overall Score
Norton 360	68
Kaspersky PURE 2.0	57
Trend Micro Maximum Security 2013	48
Bitdefender Total Security 2013	43
McAfee Total Protection 2013	39

#### **Internet Security Software (SSD)**

In the following table the highest possible score attainable is 20; in a hypothetical situation where a product has attained first place in all 5 (SSD) metrics. Total Security products have been ranked by their overall scores:

Product Name	Overall Score
Norton Internet Security 2013	16
Bitdefender Internet Security 2013	15
Trend Micro Internet Security 2013	12
Kaspersky Internet Security 2013	11
McAfee Internet Security 2013	6

### **Products and Versions**

Unless otherwise specified, we have tested the full, retail release of the newest generation (2013 versions) of security products. The names and versions of products which were tested can be found below from each category table:

#### **Internet Security Software**

Manufacturer	Product Name	Release Year	Product Version	Date Tested
Symantec Corporation	Norton Internet Security 2013	2012	20.2.0.19	Dec 2012
G Data Software AG	G Data InternetSecurity 2013	2012	23.0.0.19	Jul 2012
Avast Software a.s.	Avast! Internet Security 7	2012	7.0.1456	Aug 2012
SOFTWIN	Bitdefender Internet Security 2013	2012	16.16.0.1349	Aug 2012
Kaspersky Lab	Kaspersky Internet Security 2013	2012	13.0.1.4190	Aug 2012
Panda Security SL	Panda Internet Security 2013	2012	18.00.01	Sep 2012
McAfee, Inc.	McAfee Internet Security 2013	2012	12.0.637	Sep 2012
AVG Technologies	AVG Internet Security 2013	2012	2013.0.2677	Sep 2012
Trend Micro Inc.	Trend Micro Titanium Internet Security 2013	2012	6.0.1215	Oct 2012
F-Secure Corporation	F-Secure Internet Security 2013	2012	12.71 Build 102	Dec 2012

#### **Antivirus Software**

Manufacturer	Product Name	Release Year	Product Version	Date Tested
Symantec Corporation	Norton AntiVirus 2013	2012	20.2.0.19	Dec 2012
G Data Software AG	G Data Antivirus 2013	2012	22.0.2.25	Aug 2012
Avast Software a.s.	Avast! Pro Antivirus 7	2012	7.0.1456	Aug 2012
Microsoft Corporation	Microsoft Security Essentials	2012	4.0.1526.0	Aug 2012
Kaspersky Lab	Kaspersky Anti-Virus 2013	2012	13.0.1.4190	Aug 2012
McAfee, Inc.	McAfee Antivirus Plus	2012	12.0.637	Oct 2012
AVG Technologies	AVG Anti-Virus 2013	2012	2013.0.2677	Oct 2012
Panda Security SL	Panda Antivirus Pro 2013	2012	12.0.0.1	Oct 2012
Trend Micro Inc.	Trend Micro Titanium 2013	2012	6.0.1215	Oct 2012
Quick Heal	Quick Heal Pro Antivirus 2013	2012	14.00.7.0.0.1	Oct 2012
Avast Software a.s.	Avast! Free Antivirus 7	2012	7.0.1473	Oct 2012
Panda Security SL	Panda Clout Antivirus FREE 2013	2012	2.0.1	Oct 2012
Avira Operations GmbH & Co. KG	Avira Antivirus Free 2013	2012	13.0.0.2832	Nov 2012

### **Total Security Software**

Manufacturer	Product Name	Release Year	Product Version	Date Tested
Symantec Corporation	Norton 360	2012	20.2.0.19	Dec 2012
Trend Micro Inc.	Trend Micro Maximum Security 2013	2012	6.0.1215	Oct 2012
Kaspersky Lab	Kaspersky PURE 2.0	2012	12.0.1.288	Aug 2012
BitDefender	BitDefender Total Security 2013	2012	16.16.0.1348	Aug 2012
McAfee, Inc	McAfee Total Protection 2013	2012	16.1.140	Dec 2012

# **Performance Metrics Summary**

We have selected a set of objective metrics which provide a comprehensive and realistic indication of the areas in which an antivirus may impact system performance for end users. Our metrics test the impact of the antivirus software on common tasks that end-users would perform on a daily basis.

All of PassMark Software's test methods can be replicated by third parties using the same environment to obtain similar benchmark results. Detailed descriptions of the methodologies used in our tests are available as "Appendix 2 – Methodology Description" of this report.

#### **Benchmark 1 – Boot Time**

This metric measures the amount of time taken for the machine to boot into the operating system. Security software is generally launched at Windows startup, adding an additional amount of time and delaying the startup of the operating system. Shorter boot times indicate that the application has had less impact on the normal operation of the machine.

#### Benchmark 2 – Scan Time

All antivirus solutions have functionality designed to detect viruses and various other forms of malware by scanning files on the system. This metric measured the amount of time required to scan a set of clean files. Our sample file set comprised a total file size of 982 MB and was made up of files that would typically be found on end-user machines, such as media files, system files and Microsoft Office documents.

#### Benchmark 3 – User Interface Launch Time

This metric provides an objective indication as to how responsive a security product appears to the user, by measuring the amount of time it takes for the user interface of the antivirus software to launch from Windows. To allow for caching effects by the operating system, both the initial launch time and the subsequent launch times were measured. Our final result is an average of these two measurements.

#### Benchmark 4 – Memory Usage during System Idle

This metric measures the amount of memory (RAM) used by the product while the machine and antivirus software are in an idle state. The total memory usage was calculated by identifying all antivirus software processes and the amount of memory used by each process.

The amount of memory used while the machine is idle provides a good indication of the amount of system resources being consumed by the antivirus software on a permanent basis. Better performing products occupy less memory while the machine is idle.

#### **Benchmark 5 – Browse Time**

It is common behavior for security products to scan data for malware as it is downloaded from the internet or intranet. This behavior may negatively impact browsing speed as products scan web content for malware. This metric measures the time taken to browse a set of popular internet sites to consecutively load from a local server in a user's browser window.

#### **Benchmark 6 – Internet Explorer Launch Time**

This metric is one of many methods to objectively measure how much a security product impacts on the responsiveness of the system. This metric measures the amount of time it takes to launch the user interface of Internet Explorer 8. To allow for caching effects by the operating system, both the initial launch time and the subsequent launch times were measured. Our final result is an average of these two measurements.

#### **Benchmark 7 – Installation Time**

The speed and ease of the installation process will strongly influence the user's first impression of the antivirus software. This test measures the minimum installation time required by the antivirus software to be fully functional and ready for use by the end user. Lower installation times represent antivirus products which are quicker for a user to install.

#### Benchmark 8 – Installation Size

In offering new features and functionality to users, antivirus software products tend to increase in size with each new release. Although new technologies push the size limits of hard drives each year, the growing disk space requirements of common applications and the increasing popularity of large media files (such as movies, photos and music) ensure that a product's installation size will remain of interest to home users.

This metric aims to measure a product's total installation size. This metric is defined as the total disk space consumed by all new files added during a product's installation.

#### Benchmark 9 - Registry Keys Added

A large registry increases a machine's use of resources. This may negatively impact system performance, especially on much older machines. This test measures the amount of keys and values added to registry, after rebooting the test machines, following a successful product installation. Lower numbers mean that a product has added fewer keys during installation and had less impact on the registry.

#### Benchmark 10 - File Copy, Move and Delete

This metric measures the amount of time taken to move, copy and delete a sample set of files. The sample file set contains several types of file formats that a Windows user would encounter in daily use. These formats include documents (e.g. Microsoft Office documents, Adobe PDF, Zip files, etc), media formats (e.g. images, movies and music) and system files (e.g. executables, libraries, etc).

#### **Benchmark 11 – Installing Third Party Applications**

This metric measures the amount of time taken to install and uninstall third party programs. The installation speed of third party applications may be impacted by antivirus behavior such as heuristics or real time malware scanning.

#### **Benchmark 12 – Network Throughput**

The metric measures the amount of time taken to download a variety of files from a local server using the HyperText Transfer Protocol (HTTP), which is the main protocol used on the web for browsing, linking and data transfer. Files used in this test include file formats that users would typically download from the web, such as images, archives, music files and movie files.

#### Benchmark 13 - File Format Conversion

This test measures the amount of time taken to convert an MP3 file to a WAV and subsequently, convert the same MP3 file to a WMA format.

#### Benchmark 14 - File Compression and Decompression

This metric measures the amount of time taken to compress and decompress different types of files. Files formats used in this test included documents, movies and images.

#### Benchmark 15 - File Write, Open and Close

This benchmark was derived from Oli Warner's File I/O test at <a href="http://www.thepcspy.com">http://www.thepcspy.com</a> (please see *Reference #1: What Really Slows Windows Down*). This metric measures the amount of time taken to write a file, then open and close that file.

#### Benchmark 16 - PE Scan Time

All antivirus solutions have functionality designed to detect viruses and various other forms of malware by scanning files on the system. This metric measured the amount of time required to scan a set of PE (Portable Executable) files. Our sample file set comprised a total file size of 2.03GB and consisted of .exe (329MB), .dll (920MB) and .sys files (827MB).

#### Benchmark 17 – File Copy Disk To Disk


This test measures the amount of time taken to copy files between two local drives. The data set comprised a total file size of 5.44GB, and the formats used included documents, movies, images and executables.

# **Internet Security Software (HDD) – Test Results**

In the following charts, we have highlighted the results we obtained for Norton Internet Security in yellow. The average has also been highlighted in blue for ease of comparison.


#### **Benchmark 1 – Boot Time**

The following chart compares the average time taken for the system to boot (from a sample of five boots) for each Internet Security product tested. Products with lower boot times are considered better performing products in this category.




#### Benchmark 2 - Scan Time

The following chart compares the average time taken to scan a set of 6159 files (totaling 982 MB) for each Internet Security product tested. This time is calculated by averaging the initial (Run 1) and subsequent (Runs 2-5) scan times. Products with lower scan times are considered better performing products in this category.



#### Benchmark 3 – User Interface Launch Time

The following chart compares the average time taken to launch a product's user interface. Products with lower launch times are considered better performing products in this category.




#### Benchmark 4 - Memory Usage during System Idle

The following chart compares the average amount of RAM in use by an Internet Security product during a period of system idle. This average is taken from a sample of ten memory snapshots taken at roughly 60 seconds apart after reboot. Products with lower idle RAM usage are considered better performing products in this category.




#### Benchmark 5 - Browse Time

The following chart compares the average time taken for Internet Explorer to successively load a set of popular websites through the local area network from a local server machine. Products with lower browse times are considered better performing products in this category.




#### **Benchmark 6 – Internet Explorer Launch Time**

The following chart compares the average launch times of Internet Explorer after rebooting the machine for each Internet Security product we tested. Products with lower launch times are considered better performing products in this category.




#### **Benchmark 7 – Installation Time**

The following chart compares the minimum installation time it takes for Internet Security products to be fully functional and ready for use by the end user. Products with lower installation times are considered better performing products in this category.




#### **Benchmark 8 - Installation Size**

The following chart compares the total size of files added during the installation of Internet Security products. Products with lower installation sizes are considered better performing products in this category.




#### Benchmark 9 – Registry Keys Added

The following chart compares the amount of Registry Keys created during product installation for each Internet Security product tested. Products with lower key counts are considered better performing products in this category.




#### Benchmark 10 - File Copy, Move and Delete

The following chart compares the average time taken to copy, move and delete several sets of sample files for each Internet Security product tested. Products with lower times are considered better performing products in this category.




#### **Benchmark 11 - Installation of Third Party Applications**

The following chart compares the average time taken to install 3 different third party applications for each Internet Security product tested. Products with lower times are considered better performing products in this category.




#### Benchmark 12 - Network Throughput

The following chart compares the average time to download a sample set of common file types for each Internet Security product tested. Products with lower times are considered better performing products in this category.




#### **Benchmark 13 - File Format Conversion**

The following chart compares the average time it takes for five sample files to be converted from one file format to another (MP3 ↔ WMA, MP3 ↔ WAV) for each Internet Security product tested. Products with lower times are considered better performing products in this category.




#### **Benchmark 14 – File Compression and Decompression**

The following chart compares the average time it takes for sample files to be compressed and decompressed for each Internet Security product tested. Products with lower times are considered better performing products in this category.



#### Benchmark 15 - File Write, Open and Close

The following chart compares the average time it takes for a file to be written to the hard drive then opened and closed 180,000 times, for each Internet Security product tested. Products with lower times are considered better performing products in this category.




#### Benchmark 16 - PE Scan Time

The following chart compares the average time taken to scan a set of 6351 portable executable files (totaling 2076 MB) for each Internet Security product tested. This time is calculated by averaging the initial (Run 1) and subsequent (Runs 2-5) scan times. Products with lower scan times are considered better performing products in this category.



#### Benchmark 17 – File Copy Disk to Disk

The following chart compares the average time taken to copy a total of 8,501 files, with a total file size of 5.44GB files, from one local drive to another local drive for each Internet Security product tested. The test was performed 5 times, and the average of all 5 runs was taken as the result. Products with lower times are considered better performing products in this category.




# **Antivirus Software (HDD) – Test Results**

In the following charts, we have highlighted the results we obtained for Norton AntiVirus in yellow. The average has also been highlighted in blue for ease of comparison.


#### **Benchmark 1 – Boot Time**

The following chart compares the average time taken for the system to boot (from a sample of five boots) for each Antivirus product tested. Products with lower boot times are considered better performing products in this category.




#### Benchmark 2 - Scan Time

The following chart compares the average time taken to scan a set of 6159 files (totaling 982 MB) for each Antivirus product tested. This time is calculated by averaging the initial (Run 1) and subsequent (Runs 2-5) scan times. Products with lower scan times are considered better performing products in this category.




#### Benchmark 3 – User Interface Launch Time

The following chart compares the average time taken to launch a product's user interface. Products with lower launch times are considered better performing products in this category.




#### Benchmark 4 - Memory Usage during System Idle

The following chart compares the average amount of RAM in use by an Antivirus product during a period of system idle. This average is taken from a sample of ten memory snapshots taken at roughly 60 seconds apart after reboot. Products with lower idle RAM usage are considered better performing products in this category.




#### Benchmark 5 - Browse Time

The following chart compares the average time taken for Internet Explorer to successively load a set of popular websites through the local area network from a local server machine. Products with lower browse times are considered better performing products in this category.




#### **Benchmark 6 – Internet Explorer Launch Time**

The following chart compares the average launch times of Internet Explorer after rebooting the machine for each Antivirus product we tested. Products with lower launch times are considered better performing products in this category.




### **Benchmark 7 – Installation Time**

The following chart compares the minimum installation time it takes for Antivirus products to be fully functional and ready for use by the end user. Products with lower installation times are considered better performing products in this category.




### **Benchmark 8 - Installation Size**

The following chart compares the total size of files added during the installation of Antivirus products. Products with lower installation sizes are considered better performing products in this category.




## Benchmark 9 – Registry Keys Added

The following chart compares the amount of Registry Keys created during product installation for each Antivirus product tested. Products with lower key counts are considered better performing products in this category.




## Benchmark 10 - File Copy, Move and Delete

The following chart compares the average time taken to copy, move and delete several sets of sample files for each Antivirus product tested. Products with lower times are considered better performing products in this category.



## **Benchmark 11 – Installation of Third Party Applications**

The following chart compares the average time taken to install a third party application for each Antivirus product tested. Products with lower times are considered better performing products in this category.




## Benchmark 12 - Network Throughput

The following chart compares the average time to download a sample set of common file types for each Antivirus product tested. Products with lower times are considered better performing products in this category.




### **Benchmark 13 - File Format Conversion**

The following chart compares the average time it takes for five sample files to be converted from one file format to another (MP3 ↔ WMA, MP3 ↔ WAV) for each Antivirus product tested. Products with lower times are considered better performing products in this category.




## Benchmark 14 - File Compression and Decompression

The following chart compares the average time it takes for sample files to be compressed and decompressed for each Antivirus product tested. Products with lower times are considered better performing products in this category.




## Benchmark 15 - File Write, Open and Close

The following chart compares the average time it takes for a file to be written to the hard drive then opened and closed 180,000 times, for each Antivirus product tested. Products with lower times are considered better performing products in this category.




### **Benchmark 16 - PE Scan Time**

The following chart compares the average time taken to scan a set of 6351 portable executable files (totaling 2076 MB) for each Antivirus product tested. This time is calculated by averaging the initial (Run 1) and subsequent (Runs 2-5) scan times. Products with lower scan times are considered better performing products in this category



## Benchmark 17 – File Copy Disk to Disk

The following chart compares the average time taken to copy a set of files from one local drive to another local drive for each Antivirus product tested. The test was performed 5 times, and the average of all 5 runs was taken as the result. Products with lower times are considered better performing products in this category.




# **Total Security Software (HDD) – Test Results**

In the following charts, we have highlighted the results we obtained for Norton 360 in yellow. The average has also been highlighted in blue for ease of comparison.


### Benchmark 1 - Boot Time

The following chart compares the average time taken for the system to boot (from a sample of five boots) for each Total Security product tested. Products with lower boot times are considered better performing products in this category.




### Benchmark 2 - Scan Time

The following chart compares the average time taken to scan a set of 6159 files (totaling 982 MB) for each Total Security product tested. This time is calculated by averaging the initial (Run 1) and subsequent (Runs 2-5) scan times. Products with lower scan times are considered better performing products in this category




### **Benchmark 3 – User Interface Launch Time**

The following chart compares the average time taken to launch a product's user interface. Products with lower launch times are considered better performing products in this category.




## Benchmark 4 - Memory Usage during System Idle

The following chart compares the average amount of RAM in use by a Total Security product during a period of system idle. This average is taken from a sample of ten memory snapshots taken at roughly 60 seconds a part after reboot. Products with lower idle RAM usage are considered better performing products in this category.




### Benchmark 5 - Browse Time

The following chart compares the average time taken for Internet Explorer to successively load a set of popular websites through the local area network from a local server machine. Products with lower browse times are considered better performing products in this category.




## **Benchmark 6 – Internet Explorer Launch Time**

The following chart compares the average launch times of Internet Explorer after rebooting the machine for each Total Security product we tested. Products with lower launch times are considered better performing products in this category.




### **Benchmark 7 – Installation Time**

The following chart compares the minimum installation time it takes for Total Security products to be fully functional and ready for use by the end user. Products with lower installation times are considered better performing products in this category.




### Benchmark 8 - Installation Size

The following chart compares the total size of files added during the installation of Total Security products. Products with lower installation sizes are considered better performing products in this category.




## Benchmark 9 - Registry Keys Added

The following chart compares the amount of Registry Keys created during product installation for each Total Security product tested. Products with lower key counts are considered better performing products in this category.




## Benchmark 10 - File Copy, Move and Delete

The following chart compares the average time taken to copy, move and delete several sets of sample files for each Total Security product tested. Products with lower times are considered better performing products in this category.




## **Benchmark 11 – Installation of Third Party Applications**

The following chart compares the average time taken to install a third party application for each Total Security product tested. Products with lower times are considered better performing products in this category.




## Benchmark 12 - Network Throughput

The following chart compares the average time to download a sample set of common file types for each Total Security product tested. Products with lower times are considered better performing products in this category.




### Benchmark 13 - File Format Conversion

The following chart compares the average time it takes for five sample files to be converted from one file format to another (MP3 ↔ WMA, MP3 ↔ WAV) for each Total Security product tested. Products with lower times are considered better performing products in this category.




## Benchmark 14 - File Compression and Decompression

The following chart compares the average time it takes for sample files to be compressed and decompressed for each Total Security product tested. Products with lower times are considered better performing products in this category.




## Benchmark 15 - File Write, Open and Close

The following chart compares the average time it takes for a file to be written to the hard drive then opened and closed 180,000 times, for each Total Security product tested. Products with lower times are considered better performing products in this category.




### Benchmark 16 - PE Scan Time

The following chart compares the average time taken to scan a set of 6351 portable executable files (totaling 2076 MB) for each Total Security product tested. This time is calculated by averaging the initial (Run 1) and subsequent (Runs 2-5) scan times. Products with lower scan times are considered better performing products in this category



## Benchmark 17 – File Copy Disk to Disk

The following chart compares the average time taken to copy a set of files from one local drive to another local drive for each Total Security product tested. The test was performed 5 times, and the average of all 5 runs was taken as the result. Products with lower times are considered better performing products in this category.




# Internet Security Software (SSD) – Test Results

In the following charts, we have highlighted the results we obtained for Norton Internet Security 2013 in yellow. The average has also been highlighted in blue for ease of comparison.


### Benchmark 1 - Boot Time

The following chart compares the average time taken for the system to boot (from a sample of five boots) for each Internet Security product tested. Products with lower boot times are considered better performing products in this category.




### Benchmark 2 – Scan Time

The following chart compares the average time taken to scan a set of 6159 files (totaling 982 MB) for each Internet Security product tested. This time is calculated by averaging the initial (Run 1) and subsequent (Runs 2-5) scan times. Products with lower scan times are considered better performing products in this category




## Benchmark 10 - File Copy, Move and Delete

The following chart compares the average time taken to copy, move and delete several sets of sample files for each Internet Security product tested. Products with lower times are considered better performing products in this category.



## Benchmark 17 – File Copy Disk to Disk

The following chart compares the average time taken to copy a set of files from one local drive to another local drive for each Internet Security product tested. The test was performed 5 times, and the average of all 5 runs was taken as the result. Products with lower times are considered better performing products in this category.



## **Disclaimer and Disclosure**

This report only covers versions of products that were available at the time of testing. The tested versions are as noted in the "Products and Versions" section of this report. The products we have tested are not an exhaustive list of all products available in these very competitive product categories.

### **Disclaimer of Liability**

While every effort has been made to ensure that the information presented in this report is accurate, PassMark Software Pty Ltd assumes no responsibility for errors, omissions, or out-of-date information and shall not be liable in any manner whatsoever for direct, indirect, incidental, consequential, or punitive damages resulting from the availability of, use of, access of, or inability to use this information.

### **Disclosure**

Symantec Corporation funded the production of this report, selected the test metrics and list of products to include in this report, and supplied some of the test scripts used for the tests.

### **Trademarks**

All trademarks are the property of their respective owners.

## **Contact Details**

### **PassMark Software Pty Ltd**

Suite 202, Level 2 35 Buckingham St. Surry Hills, 2010 Sydney, Australia

Phone + 61 (2) 9690 0444

Fax + 61 (2) 9690 0445

Web www.passmark.com

#### **Download Location**

An electronic copy of this report can be found at the following location:

http://www.passmark.com/tpsreport13

# **Appendix 1 – Test Environment**

For our testing, PassMark Software used a test environment running Windows 7 Ultimate (64-bit) SP1 with the following hardware specifications:

## Windows 7 (64-bit) System

CPU: Intel Core i7 920 Quad Core @ 2.67GHz

Video Card: nVidia GeForce 8800 GT

Motherboard: Intel x58 Motherboard

RAM: 6GB DDR3 RAM

HDD: Western Digital 500GB 7200RPM

Network: Gigabit (1GB/s) switch

# **Appendix 2 – Methodology Description**

### **Windows 7 Image Creation**

As with testing on Windows Vista, *Norton Ghost* was used to create a "clean" baseline image prior to testing. Our aim is to create a baseline image with the smallest possible footprint and reduce the possibility of variation caused by external operating system factors.

The baseline image was restored prior to testing of each different product. This process ensures that we install and test all products on the same, "clean" machine.

The steps taken to create the base Windows 7 image are as follows:

- 1. Installation and activation of Windows 7 Ultimate Edition.
- 2. Disabled Automatic Updates.
- Changed User Account Control settings to "Never Notify".
- 4. Disable Windows Defender automatic scans to avoid unexpected background activity.
- 5. Disable the Windows firewall to avoid interference with security software.
- **6.** Installed Norton Ghost for imaging purposes.
- **7.** Disabled *Superfetch* to ensure consistent results.
- 8. Installed HTTP Watch for Browse Time testing.
- 9. Installed Windows Performance Toolkit x64 for Boot Time testing.
- **10.** Installed Active Perl for interpretation of some test scripts.
- 11. Install OSForensics for testing (Installation Size and Registry Key Count tests) purposes.
- 12. Disabled updates, accelerators and compatibility view updates in Internet Explorer 8.
- 13. Update to Windows Service Pack 1
- 14. Created a baseline image using Norton Ghost.

#### Benchmark 1 - Boot Time

PassMark Software uses tools available from the Windows Performance Toolkit version 4.6 (as part of the Microsoft Windows 7 SDK obtainable from the Microsoft Website) with a view to obtaining more precise and consistent boot time results on the Windows 7 platform.

The boot process is first optimized with **xbootmgr.exe** using the command "xbootmgr.exe -trace boot – prepSystem" which prepares the system for the test over six optimization boots. The boot traces obtained from the optimization process are discarded.

After boot optimization, the benchmark is conducted using the command "xbootmgr.exe -trace boot -numruns 5". This command boots the system five times in succession, taking detailed boot traces for each boot cycle.

Finally, a post-processing tool was used to parse the boot traces and obtain the *BootTimeViaPostBoot* value. This value reflects the amount of time it takes the system to complete all (and only) boot time processes. Our final result is an average of five boot traces.

### Benchmark 2 - Scan Time

Scan Time is the time it took for each product to scan a set of sample files. The sample used was identical in all cases and contained a mixture of system files and Office files. In total there were 6159 files whose combined size was 982 MB. Most of these files come from the Windows system folders. As the file types can influence scanning speed, the breakdown of the main file types, file numbers and total sizes of the files in the sample set is given here:

File Extension	Number of Files	File Size
.dll	2589	490MB
.exe	695	102MB
.sys	332	23MB
.gif	302	1MB
.doc	281	64MB
.wmf	185	2MB
.png	149	2MB
.html	126	1MB
.nls	80	6MB
.jpg	70	1MB
.ini	59	2MB
.ico	58	<1MB
.mof	43	6MB
.ax	39	4MB
.xls	38	3MB
.ime	35	5MB
.drv	31	1MB
.txt	31	1MB
.chm	30	6MB
.cpl	29	4MB
.mfl	29	3MB
.inf	26	2MB
.hlp	22	3MB
.imd	20	18MB
.py	20	<1MB
.msc	18	1MB
.vbs	18	1MB
.xml	18	1MB
.rtf	16	62MB
.ocx	16	4MB
.tsp	14	1MB
.com	14	<1MB
.xsl	14	<1MB
.h	13	<1MB
.vsd	12	2MB
.scr	12	2MB
.aw	12	2MB
.js	12	1MB
.zip	11	25MB
.lex	9	10MB
.ppt	9	4MB
.acm	9	1MB
.wav	7	5MB
Total	6159	982

This scan was run without launching the product's user interface, by right-clicking the test folder and choosing the "Scan Now" option. To record the scan time, we have used product's built-in scan timer or reporting system. Where this was not possible, scan times were taken manually with a stopwatch.

For each product, five samples were taken with the machine rebooted before each sample to clear any caching effects by the operating systems.

In 2009, we noticed many more products showing a substantial difference between the initial scan time (first scan) and subsequent scan times (scans 2 to 5). We believe this behavior is due to products themselves caching recently scanned files.

As a result of this mechanism, we have averaged the four subsequent scan times to obtain an average subsequent scan time. Our final result for this test is an average of the subsequent scan average and the initial scan time.

### **Benchmark 3 – User Interface Launch Time**

The launch time of a product's user interface was taken using **AppTimer** (v1.0.1006). For each product tested, we obtained a total of fifteen samples from five sets of three UI launches, with a reboot before each set to clear caching effects by the operating system. When compiling the results the first of each set was separated out so that there was a set of values for the initial launch after reboot and a set for subsequent launches.

We have averaged the subsequent launch times to obtain an average subsequent launch time. Our final result for this test is an average of the subsequent launch average and the initial launch time.

In some cases, *AppTimer* did not correctly record the time taken for UI launch. For instance, some applications would open their window and look like they were ready, but then continued to be unresponsive. Where the measurement from *AppTimer* appeared inaccurate, we have taken the time manually with a stop watch.

AppTimer is publically available from the PassMark Website.

### Benchmark 4 – Memory Usage during System Idle

The *Perflog++* utility was used to record process memory usage on the system at boot, and then every minute for another fifteen minutes after. This was done only once per product and resulted in a total of 15 samples. The first sample taken at boot is discarded.

The *PerfLog++* utility records memory usage of all processes, not just those of the anti-malware product. As a result of this, an anti-malware product's processes needed to be isolated from all other running system processes. To isolate relevant process, we used a program called *Process Explorer* which was run immediately upon the completion of memory usage logging by *PerfLog++*. *Process Explorer* is a Microsoft Windows Sysinternals software tool which shows a list of all DLL processes currently loaded on the system.

### **Benchmark 5 – Browse Time**

We used a script in conjunction with *HTTPWatch* (Basic Edition, version 6.1) to record the amount of time it takes for a set of 106 'popular' websites to load consecutively from a local server. This script feeds a list of URLs into *HTTPWatch*, which instructs the browser to load pages in sequence and monitors the amount of time it takes for the browser to load all items on one page.

For this test, we have used Internet Explorer 9 (Version 9.0.8112.16421) as our browser.

The set of websites used in this test include front pages of high traffic pages. This includes shopping, social, news, finance and reference websites.

The Browse Time test is executed five times and our final result is an average of these five samples. The local server is restarted between different products and one initial 'test' run is conducted prior to testing to install *Adobe Flash Player*, an add-on which is used by many popular websites.

### **Benchmark 6 – Internet Explorer Launch Time**

The average launch time of Internet Explorer interface was taken using *AppTimer*. This test was practically identical to the User Interface launch time test. For each product tested, we obtained a total of fifteen samples from five sets of three Internet Explorer launches, with a reboot before each set to clear caching effects by the operating system. When compiling the results the first of each set was separated out so that there was a set of values for the initial launch after reboot and a set for subsequent launches.

For this test, we have used *Internet Explorer 8* (Version 8.0.6001.18783) as our test browser.

We have averaged the subsequent launch times to obtain an average subsequent launch time. Our final result for this test is an average of the subsequent launch average and the initial launch time.

### Benchmark 7 - Installation Time

This test measures the minimum Installation Time a product requires to be fully functional and ready for use by the end user. Installation time can usually be divided in three major phases:

- The Extraction and Setup phase consists of file extraction, the EULA prompt, product activation and user configurable options for installation.
- The File Copy phase occurs when the product is being installed; usually this phase is indicated by a progress bar.
- The Post-Installation phase is any part of the installation that occurs after the File Copy phase. This phase varies widely between products; the time recorded in this phase may include a required reboot to finalize the installation or include the time the program takes to become idle in the system tray.

To reduce the impact of disk drive variables, each product was copied to the Desktop before initializing installation. Each step of the installation process was manually timed with a stopwatch and recorded in as much detail as possible. Where input was required by the end user, the stopwatch was paused and the input noted in the raw results in parenthesis after the phase description.

Where possible, all requests by products to pre-scan or post-install scan were declined or skipped. Where it was not possible to skip a scan, the time to scan was included as part of the installation time. Where an optional component of the installation formed a reasonable part of the functionality of the software, it was also installed (e.g. website link checking software as part of an Internet Security Product).

Installation time includes the time taken by the product installer to download components required in the installation. This may include mandatory updates or the delivery of the application itself from a download manager. We have noted in our results where a product has downloaded components for product installation.

We have excluded product activation times due to network variability in contacting vendor servers or time taken in account creation.

### Benchmark 8 - Installation Size

A product's Installation Size was previously defined as the difference between the initial snapshot of the Disk Space (C: drive) before installation and the subsequent snapshot taken after the product is installed on the system. Although this is a widely used methodology, we noticed that the results it yielded were not always reproducible in Vista due to random OS operations that may take place between the two snapshots. We improved the Installation Size methodology by removing as many Operating System and disk space variables as possible.

Using PassMark's **OSForensics** we created initial and post-installation disk signatures for each product. These disk signatures recorded the amount of files and directories, and complete details of all files on that drive (including file name, file size, checksum, etc) at the time the signature was taken.

The initial disk signature was taken immediately prior to installation of the product. A subsequent disk signature was taken immediately following a manual update and system reboot after product installation. Using **OSForensics**, we compared the two signatures and calculated the total disk space consumed by files that were new, modified, and deleted during product installation. Our result for this metric reflects the total size of all newly added files during installation.

### Benchmark 9 – Registry Key Count

This test measures the amount of keys and values added to registry, after rebooting the test machine following a successful product installation. The test was conducted using PassMark's **OSForensics**, to count the number of keys, errors and values that were added under HKEY\_LOCAL\_MACHINE and HKEY\_USERS. The Create Signature feature is used to take a before and after signature of these folders, and the signatures are then compared so that the new keys can be identified.

### Benchmarks 10-15 – Real-Time Performance

We used a single script in testing Benchmarks 10-15. The script consecutively executes tests for Benchmarks 10-15. The script times each phase in these benchmarks using *CommandTimer.exe* and appends results to a log file.

### Benchmarks 10 - File Copy, Move and Delete

This test measures the amount of time required for the system to copy, move and delete samples of files in various file formats. This sample was made up of 812 files over 760,867,636 bytes and can be categorized as documents [26% of total], media files [54% of total] and PE files (i.e. System Files) [20% of total].

The breakdown of the main file types, file numbers and total sizes of the files in the sample set is shown in the following table:

File format Number Size (bytes)

DOC	8	30,450,176
DOCX	4	13,522,409
PPT	3	5,769,216
PPTX	3	4,146,421
XLS	4	2,660,352
XLSX	4	1,426,054
PDF	73	136,298,049
ZIP	4	6,295,987
7Z	1	92,238
JPG	351	31,375,259
GIF	6	148,182
MOV	7	57,360,371
RM	1	5,658,646
AVI	8	78,703,408
WMV	5	46,126,167
MP3	28	191,580,387
EXE	19	2,952,914
DLL	104	29,261,568
AX	1	18,432
CPL	2	2,109,440
CPX	2	4,384
DRV	10	154,864
ICO	1	107,620
MSC	1	41,587
NT	1	1,688
ROM	2	36,611
SCR	2	2,250,240
SYS	1	37,528,093
TLB	3	135,580
TSK	1	1,152
UCE	1	22,984
EXE	19	2,952,914
DLL	104	29,261,568
AX	1	18,432
CPL	2	2,109,440
CPX	2	4,384
DRV	10	154,864

ICO	1	107,620
MSC	1	41,587
NT	1	1,688
ROM	2	36,611
SCR	2	2,250,240
SYS	1	37,528,093
TLB	3	135,580
TSK	1	1,152
UCE	1	22,984
Total	812	760,867,636

This test was conducted five times to obtain the average time to copy, move and delete the sample files, with the test machine rebooted between each sample to remove potential caching effects.

### **Benchmark 11 – Third Party Program Installation**

This test measured how much time was required to install and uninstall a third party application. For this test, *CommandTimer.exe* timed how long it took to install and uninstall the following applications on the test machine:

- Firefox 3.6.3 (11,909 KB) (MSI File)
- Microsoft .NET 3.5 (34,121 KB) (MSI File)
- Steam (1,551 KB) (MSI File)

This test was conducted five times to obtain the average time to install/uninstall the above third party programs, with the test machine rebooted between each sample to remove potential caching effects.

### Benchmark 12 - Network Throughput

This benchmark measured how much time was required to download a sample set of binary files of various sizes and types over a 100MB/s network connection. The files were hosted on a server machine running Windows Server 2008 and IIS 7. *CommandTimer.exe* was used in conjunction with *GNU Wget* (version 1.10.1) to time and conduct the download test.

The complete sample set of files was made up of 553,638,694 bytes over 484 files and two file type categories: media files [74% of total] and documents [26% of total]. The breakdown of the file types, file numbers and total sizes of the files in the sample set is shown in the following table:

File format	Number	Size (bytes)
JPEG	343	30,668,312
GIF	9	360,349
PNG	5	494,780
MOV	7	57,360,371
RM	1	5,658,646
AVI	8	78,703,408

WMV	5	46,126,167
MP3	28	191,580,387
PDF	73	136,298,049
ZIP	4	6,295,987
7Z	1	92,238
Total	484	553,638,694

This test was conducted five times to obtain the average time to download this sample of files, with the test machine rebooted between each sample to remove potential caching effects.

### Benchmark 13 – File Format Conversion (MP3 → WAV, MP3 → WMA)

This test measured how much time was required to convert five (5) different MP3 files into WAV files and subsequently, convert the same MP3 samples into a WMA files. The total size of the five (5) MP3s used was 25,870,899 bytes.

To encode the MP3 into another format, we used an application called *ffmpeg.exe*. The format conversion process was timed using *CommandTimer.exe*.

This test was conducted five times to obtain the average conversion speed between these formats, with the test machine rebooted between each sample to remove potential caching effects.

### Benchmark 14 – File Compression and Decompression

This test measured the amount of time required to compress and decompress a sample set of files. For this test, we used a subset of the media and documents files used in the *File Copy, Move and Delete* benchmark. *CommandTimer.exe* recorded the amount of time required for *7zip.exe* to compress the files into a \*.zip and subsequently decompress the created \*.zip file.

This subset comprised 1,218 files over 783 MB. The breakdown of the file types, file numbers and total sizes of the files in the sample set is shown in the following table:

File Type	File Number	Total Size
.xls	13	9.23 MB
.xlsx	9	3.51 MB
.ppt	9	7.37 MB
.pptx	11	17.4 MB
.doc	17	35.9 MB
.docx	19	24.5 MB
.gif	177	1.10 MB
.jpg	737	66.2 MB
.png	159	48.9 MB
.mov	7	54.7 MB

.rm	1	5.39 MB
.avi	46	459 MB
.wma	11	48.6 MB
.avi	46	459 MB
.wma	11	48.6 MB
Total	1218	783 MB

This test was conducted five times to obtain the average file compression and decompression speed, with the test machine rebooted between each sample to remove potential caching effects.

## Benchmark 15 – File Write, Open and Close

This benchmark was derived from Oli Warner's File I/O test at <a href="http://www.thepcspy.com">http://www.thepcspy.com</a> (please see *Reference* #1: What Really Slows Windows Down).

For this test, we developed *OpenClose.exe*, an application that looped writing a small file to disk, then opening and closing that file. *CommandTimer.exe* was used to time how long the process took to complete 180,000 cycles.

This test was conducted five times to obtain the average file writing, opening and closing speed, with the test machine rebooted between each sample to remove potential caching effects.

### Benchmark 16 - PE Scan Time

This test measures the on demand scan times of a file set comprised only of executable files (.exe, .dll and .sys files). We performed five scans of the sample file set, with a machine restart between each scan to remove possible caching effects. The time taken to scan the files is taken from an antivirus product's scan logs, or where logs are not available, manually with a stopwatch. Scans were launched by right clicking on the folder to be scanned.

A breakdown of the sample file set is as follows:

File Type	Number of Files	File Size
Sys Files	2174	329MB
Dll Files	2037	920MB
Exe Files	2140	827MB
Total	6351	2076MB

The final result is calculated as an average of the five samples.

### Benchmark 17 – File Copy Disk to Disk

This test measures the amount of time taken to copy files between two local drives. The data set comprised of 8,501 files with a total file size of 5.44GB, and the formats used included documents, movies, images and executables. A breakdown of the sample file set is given below:

File Extension	Number of Files	File Size
.jpg	2903	588MB
.dll	773	25MB
.exe	730	197MB
.gif	681	63MB
.wav	430	260MB
.sys	501	79MB
.png	451	27MB
.mp3	333	2157MB
.wma	585	925MB
.docx	267	81MB
.avi	247	1079MB
.doc	160	57MB
.xls	329	132MB
.ppt	97	148MB
.zip	14	177MB
Total	8501	5995MB

A total of five runs of this test were performed, with a machine restart between each run. The time taken to copy files was measured and recorded by CommandTimer.exe. All the files were copied between a folder on the local drive and a 2<sup>nd</sup> folder on a different drive. Files were deleted from the 2<sup>nd</sup> drive once the copy was complete. The final result is calculated as an average of the five samples